

TYPE

Type	Standard Performance
------	----------------------

PANEL

Screen Size	21.5"
Panel Technology	IPS
Native Resolution	1,920 x 1,080 (FHD)
Brightness	250 nit (Typ.)
Contrast Ratio	1,000:1
Dynamic CR	400,000:1
Color Gamut	BT.709 95%
Viewing Angle(H x V)	178 x 178
Color Depth	6bit, 1 6.7Million Colors
Response Time	14ms (G to G)
Surface Treatment(Haze)	25%
Operation Hours (Hours/Day)	1 6/7
Landscape	Yes

CONNECTIVITY

Input - Digital - HDMI	Yes(2), HDCP2.2
Input - Audio In	Yes(1)
Input - External Control - RS232C IN	Yes(1), Phone-jack

Input - External Control - RJ45(LAN)	Yes(1)
Input - External Control - IR IN	Yes(1), Phone-jack
Input - USB	USB2.0 Type A(1)

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	Even Bezel 1 6.3mm
Weight(Head)	3.34 kg
Monitor Dimension(W x H x D)	510.3 x 302.1 x 53.8mm
VESA™ Standard Mount Interface	100 x 100

KEY FEATURE

HW - Internal Memory	8GB
HW - Wi-Fi - Built-in	Yes
HW - Sensor - Temperature Sensor	Yes
HW - Local Key Operation	Yes
SW - webOS ver.	webOS 4.1
SW - Embedded CMS - Local Contents Scheduling	Yes
SW - Embedded CMS - Group Manager	Yes
SW - USB Plug & Play	Yes
SW - Fail over	Yes
SW - Background Image - Booting Logo Image	Yes

SW - Background Image - No Signal Image	Yes
SW - Multi-screen - PIP	Yes
SW - Multi-screen - PBP	Yes(2)
SW - Screen Share	Yes
SW - Video Tag	Yes(2)
SW - Play via URL	Yes
SW - Gapless Playback	Yes
SW - Setting Data Cloning	Yes
SW - SNMP	Yes
SW - ISM Method	Yes
SW - Status Mailing	Yes
SW - Control Manager	Yes
SW - 3rd Party Compatibility - Crestron Connected®	Yes (Network Based Control)
SW - Smart Energy Saving	Yes
SW - PM mode	Yes
SW - Wake on LAN	Yes
SW - Beacon	Yes
SW - HDMI-CEC	Yes (Compatibility may differ by equipment.)
SW - SI Server Setting	Yes
SW - webRTC	Yes
SW - Pro:Idiom	Yes

ENVIRONMENT CONDITIONS

Operation Temperature0 °C to 40 °C

Operation Humidity10 % to 80 %

POWER

Power SupplyAC 100-240V~, 50/60Hz

Power TypeBuilt-In Power

POWER CONSUMPTION

Typ.30W

Max.33W

BTU (British Thermal Unit)7.17(Typ), 7.89(Max)

SOUND

SpeakerYes(1W x 2EA)

CERTIFICATION

SafetyCB / NRTL

EMCFCC Class "A" / CE

ErPYes (EU Only)

SOFTWARE COMPATIBILITY

SuperSign CMSYes

SuperSign Control / Control+Yes / Yes

SuperSign WB	Yes
SuperSign Media Editor	Yes
Signage 365 Care	Yes (The availability can differ by region.)

ACCESSORY

Basic	Remote Controller, Power Cord, QSG, HDMI Cable, Phone to RS232C Gender, External IR, IR Sheet
-------	---